

# Kanaflex®

## KANAPOWER AT



Kanapower AT is our new abrasion resistant suction and discharge hose designed for demanding applications such as slurry systems in *micro-tunneling applications and directional boring*. Constructed of SBR rubber blended with static dissipating carbon black, it is rated to 140 P.S.I.



# Kanaflex®

## KANAPOWER AT

*Lightweight...* up to 50% lighter than conventional rubber hose

*Extra heavy duty exposed helix...* acts as a scuff guard, permits water to flow underneath, allows easy drag and provides substantial protection from outside impact and abrasion

*Braided reinforcement...* permits use under high working pressure

*Smooth bore...* provides unrestricted flow

*Heavy duty sidewall...* constructed of abrasion resistant static dissipating SBR rubber

*Flexible...* lends itself to working in much tighter spaces than conventional rubber hose



### SPECIFICATIONS: KANAPOWER AT

SIZE	OUTSIDE DIAMETER Inches	PITCH Inches	MIN. BENDING RADIUS 72°F, Inches	WORKING PRESSURE 72°F, P.S.I.	BURSTING PRESSURE 72°F, P.S.I.	VACUUM RATING 72°F, In./Hg.	WEIGHT Lbs./Ft.
3"	3.90	0.59	8.0	140	700	28	1.65
4"	5.04	0.65	10.0	140	700	28	2.85
6"	7.26	0.87	16.0	140	700	28	4.50

**Kanaflex®**  
CORPORATION

800 Woodlands Parkway  
Vernon Hills, IL 60061

DISTRIBUTED BY: